NSN 5962-01-228-9820

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-228-9820

| Body Length: |
|--|
| Between 1.230 inches and 1.285 inches |
| Body Width: |
| Between 0.510 inches and 0.545 inches |
| Body Height: |
| Between 0.135 inches and 0.165 inches |
| Operating Tempurature Range: |
| -55.0 to 125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0 to 150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and bipolar and programmable and high performance and asynchronous and schottky |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 14 input |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| -0.5 volts power source and 7.0 volts power source |
| Time Rating Per Chacteristic: |
| 35.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level |
| output |
| Memory Device Type: |
| Rom |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 24 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |