NSN 5962-01-230-2318

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-230-2318

Body Length:
1.060 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0 to 125.0 degrees celsius
Storage Tempurature Range:
-65.0 to 150.0 degrees celsius
Features Provided:
Monolithic and high speed and w/clock and burn in and electrostatic sensitive
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
10 input
Design Function And Quantity:
8 flip-flop, d-type
Case Outline Source And Designator:
D-8 mil-m-38510
Terminal Surface Treatment:
Gold or solder or tin
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Precious Material And Location:
Terminal surfaces option gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
20 printed circuit
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5962-01-230-2318

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0