## NSN 5962-01-230-3003

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-230-3003

## **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 2000.0 milliwatts **Operating Tempurature Range:** -55.0 to 140.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius **Features Provided:** Electrostatic sensitive and monolithic **Inclosure Material:** Ceramic or plastic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 9 input **Design Function And Quantity:** 1 control **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Solder or tin or gold Voltage Rating And Type Per Characteristic: 40.0 volts power source **Precious Material And Location:** Terminal surface option gold **Precious Material:** Gold **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** Yes - demil/mli

## NSN 5962-01-230-3003

Linear Microcircuit - Page 2 of 2

**Fiig:** A458a0

