NSN 5962-01-230-4544

Digital-linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-230-4544

Body Length:	
0.960 inches	
Body Width:	
Between 0.220	inches and 0.310 inches
Body Height:	
0.185 inches	
Maximum Pow	er Dissipation Rating:
450.0 milliwatts	
Operating Tem	purature Range:
-55.0/+125.0 de	grees celsius
Storage Temp	Irature Range:
-65.0/+150.0 de	grees celsius
Features Provi	ded:
Monolithic and I	nermetically sealed and positive outputs
Inclosure Mate	rial:
Ceramic and gla	ass
Inclosure Conf	iguration:
Dual-in-line	
Output Logic F	orm:
Transistor-trans	istor logic
Input Circuit P	attern:
15 input	
Design Functio	on And Quantity:
l converter, dig	jital to analog
Case Outline S	ource And Designator:
D-6 mil-m-3851	0
Terminal Surfa	ce Treatment:
Solder	
Voltage Rating	And Type Per Characteristic:
17.0 volts powe	er source
Precious Mate	rial And Location:
Terminal surfac	es gold
Precious Mate	ial:
Gold	
Test Data Docu	iment:
81349-mil-m-38	510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; exclude	s commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental a	nd performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type	And Quantity:
18 printed circu	t
Specification D	Data:
81349-mil-m-38	510/127 government specification
Shelf Life:	
N/a	

NSN 5962-01-230-4544

Digital-linear Microcircuit - Page 2 of 2



Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0