NSN 5962-01-230-4552

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-230-4552

| Body Length: | |
|---|--------------------|
| 0.390 inches | |
| Body Width: | |
| Between 0.235 inches and 0.260 inches | |
| Body Height: | |
| Between 0.045 inches and 0.085 inches | |
| Maximum Power Dissipation Rating: | |
| 6.1 watts | |
| Operating Tempurature Range: | |
| -55.0/+125.0 degrees celsius | |
| Storage Tempurature Range: | |
| -65.0/+150.0 degrees celsius | |
| Features Provided: | |
| Monolithic and schottky and low power and w/open collector | |
| Inclosure Material: | |
| Ceramic | |
| Inclosure Configuration: | |
| Flat pack | |
| Output Logic Form: | |
| Transistor-transistor logic | |
| nput Circuit Pattern: | |
| Quad 2 input | |
| Design Function And Quantity: | |
| a gate, nand | |
| Case Outline Source And Designator: | |
| F-2 mil-m-38510 | |
| Ferminal Surface Treatment: | |
| Solder | |
| Voltage Rating And Type Per Characteristic: | |
| 0.5 volts power source and 7.0 volts power source | |
| Test Data Document: | |
| 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data | a in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data | on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | |
| Terminal Type And Quantity: | |
| 14 flat leads | |
| Specification Data: | |
| 81349-mil-m-38510/300 government specification | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| Yes - demil/mli | |
| | |

NSN 5962-01-230-4552

Digital Microcircuit - Page 2 of 2

Fiig: A458a0

