NSN 5962-01-230-9208

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-230-9208 **Body Length:** 1.060 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 522.5 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Electrostatic sensitive and hermetically sealed and burn in and 3-state output and low power **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 18 input **Design Function And Quantity:** 8 transceiver **Case Outline Source And Designator:** D-8 mil-m-38510 **Time Rating Per Chacteristic:** 22.00 nanoseconds propagation delay time, low to high level output and 22.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surface option gold **Precious Material:** Gold **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Shelf Life: N/a **Unit Of Measure:**

Fiig:

A458a0

Demilitarization: Yes - demil/mli