## NSN 5962-01-231-3426

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-231-3426

Body Length:
0.540 inches
Body Width:
Between 0.245 inches and 0.300 inches
Body Height:
0.092 inches
Maximum Power Dissipation Rating:
522.5 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and 3-state output and w/enable
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
18 input
Design Function And Quantity:
8 transceiver
Case Outline Source And Designator:
F-9 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
22.00 nanoseconds propagation delay time, low to high level output and 22.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
20 flat leads
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

## NSN 5962-01-231-3426

Digital Microcircuit - Page 2 of 2

**Fiig:** A458a0

