NSN 5962-01-232-1773

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-232-1773 **Body Length:** 0.840 inches **Body Width:** 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 2.0 watts **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius **Features Provided:** Hermetically sealed and electrostatic sensitive and monolithic **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 7 input **Criticality Code Justification:** Feat **Design Function And Quantity:** 1 array, darlington transistor **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Solder or tin or gold **Special Features:** Nuclear hardness critical item **Precious Material And Location:** Terminal surface option gold **Precious Material:** Gold **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5962-01-232-1773

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0