## NSN 5962-01-232-3017

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-232-3017 **Body Length:** 0.886 inches **Body Width:** 0.310 inches **Body Height:** 0.140 inches **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius **Storage Tempurature Range:** -65.0 to 150.0 degrees celsius **Features Provided:** Monolithic and programmable and 3-state output and burn in **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 10 input **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 70.00 nanoseconds propagation delay time, low to high level output and 70.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

**Fiig:** A458a0

Yes - demil/mli