NSN 5962-01-232-6529

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-232-6529 **Body Length:** 0.400 inches **Body Width:** 0.290 inches **Body Height:** 0.080 inches **Maximum Power Dissipation Rating:** 307.2 milliwatts **Operating Tempurature Range:** +0.0/+75.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Om-51a/fr **Features Provided:** Hermetically sealed and 3-state output and w/enable and programmable and schottky **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 6 input **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** Err-060 hand pull and err-060 hand **Memory Device Type:** Rom **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 flat leads Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5962-01-232-6529

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0