Digital-linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-232-7600

| Body Length: | |
|--------------------|--|
| 0.825 inches | |
| Body Width: | |
| 0.520 inches | |
| Body Height: | |
| 0.155 inches | |
| Maximum Powe | er Dissipation Rating: |
| 585.0 milliwatts | |
| Operating Temp | burature Range: |
| -55.0/+125.0 deg | prees celsius |
| Storage Tempu | rature Range: |
| -65.0/+150.0 deg | rees celsius |
| End Application | 1: |
| 5841-01-054-854 | 10 radar signal de |
| Features Provid | led: |
| Hermetically sea | led and burn in and w/switch and hybrid |
| Inclosure Mater | ial: |
| Ceramic | |
| Inclosure Confi | guration: |
| Dual-in-line | |
| Output Logic Fo | orm: |
| Transistor-transis | stor logic |
| Input Circuit Pa | ttern: |
| 8 input | |
| Design Function | n And Quantity: |
| 1 converter, digi | tal to analog |
| Terminal Surfac | e Treatment: |
| Solder | |
| Voltage Rating | And Type Per Characteristic: |
| 18.0 volts power | rsource |
| Test Data Docu | ment: |
| 96906-mil-std-88 | 3 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type | And Quantity: |
| 14 printed circuit | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure | 2: |
| | |
| Demilitarization | : |
| Yes - demil/mli | |
| Fiig: | |
| A458a0 | |