NSN 5962-01-232-9680



Memory Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-232-9680 **Body Length:** Between 1.235 inches and 1.285 inches **Body Width:** Between 0.515 inches and 0.600 inches **Body Height:** Between 0.140 inches and 0.185 inches **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius **Storage Tempurature Range:** -65.0 to 150.0 degrees celsius **Features Provided:** Programmable and ultraviolet erasable and low power and w/enable **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 14 input **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 26.5 volts power source **Time Rating Per Chacteristic:** 450.00 nanoseconds propagation delay time, low to high level output and 450.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 24 printed circuit Shelf Life: N/a **Unit Of Measure:**

Fiig: A458a0

Demilitarization: Yes - demil/mli