Digital-linear Microcircuit - Page 1 of 1



high to low level

View Online at https://aerobasegroup.com/nsn/5962-01-234-0887

Body Length:	
0.775 inches	
Body Width:	
0.275 inches	
Body Height:	
0.145 inches	
Maximum Power Dissipation Rating:	
750.0 milliwatts	
Operating Tempurature Range:	
20.0/+85.0 degrees celsius	
Storage Tempurature Range:	
65.0/+150.0 degrees celsius	
Features Provided:	
Hermetically sealed and monolithic and high	speed and dielectric isolated
Inclosure Material:	
Ceramic	
Inclosure Configuration:	
Dual-in-line	
Output Logic Form:	
Complementary-metal oxide-semiconductor	logic
Input Circuit Pattern:	
Quad 2 input	
Design Function And Quantity:	
4 switch, analog, single pole single throw no	ormally open
Terminal Surface Treatment:	
Solder	
Voltage Rating And Type Per Characterist	ic:
40.0 volts power source	
Time Rating Per Chacteristic:	
220.00 nanoseconds propagation delay time	e, low to high level output and 185.00 nanoseconds propagation delay time,
output	
Terminal Type And Quantity:	
16 printed circuit	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
Yes - demil/mli	
Fiig:	
A458a0	