## NSN 5962-01-234-9316

Digital Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-234-9316

Body Length:
0.390 inches
Body Width:
Between 0.235 inches and 0.260 inches
Body Height:
Between 0.045 inches and 0.085 inches
Maximum Power Dissipation Rating:
6.1 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and monolithic and low power and schottky
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Hex 1 input
Design Function And Quantity:
6 gate, inverting
Case Outline Source And Designator:
F-2 mil-m-38510
Time Rating Per Chacteristic:
20.00 nanoseconds propagation delay time, low to high level output and 24.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-m-38510/300 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig: