## NSN 5962-01-234-9320

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-234-9320

Body Length:  0.390 inches  Body Width:  Between 0.235 inches and 0.260 inches  Body Height:  Between 0.045 inches and 0.085 inches  Maximum Power Dissipation Rating:  149.0 milliwatts
Body Width: Between 0.235 inches and 0.260 inches  Body Height: Between 0.045 inches and 0.085 inches  Maximum Power Dissipation Rating:  149.0 milliwatts
Between 0.235 inches and 0.260 inches  Body Height:  Between 0.045 inches and 0.085 inches  Maximum Power Dissipation Rating:  149.0 milliwatts
Body Height: Between 0.045 inches and 0.085 inches  Maximum Power Dissipation Rating:  149.0 milliwatts
Between 0.045 inches and 0.085 inches  Maximum Power Dissipation Rating:  149.0 milliwatts
Maximum Power Dissipation Rating: 149.0 milliwatts
149.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and monolithic and low power and schottky and w/clock and w/clear
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
4 input
Design Function And Quantity:
1 shift register
Case Outline Source And Designator:
F-2 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
14 flat leads
Specification Data:
81349-mil-m-38510/306 government specification
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

## NSN 5962-01-234-9320

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0