

View Online at <https://aerobasegroup.com/nsn/5962-01-234-9370>

**Body Length:**

0.390 inches

**Body Width:**

Between 0.235 inches and 0.260 inches

**Body Height:**

Between 0.045 inches and 0.085 inches

**Maximum Power Dissipation Rating:**

200.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and burn in and monolithic and positive outputs

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

Quad 2 input

**Design Function And Quantity:**

4 gate, and

**Case Outline Source And Designator:**

F-2 mil-m-38510

**Time Rating Per Characteristic:**

350.00 nanoseconds propagation delay time, low to high level output and 350.00 nanoseconds propagation delay time, high to low level output

**Precious Material And Location:**

Terminal surfaces gold

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-m-38510/170 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0