NSN 5962-01-235-0349

Linear Microcircuit - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5962-01-235-0349 |
|--|
| Body Outside Diameter: |
| Between 0.350 inches and 0.370 inches |
| Body Height: |
| Between 0.165 inches and 0.185 inches |
| Maximum Power Dissipation Rating: |
| 570.0 milliwatts |
| Operating Tempurature Range: |
| -0.0/+70.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| 4920-01-186-2452 calibration sta |
| Features Provided: |
| Hermetically sealed and monolithic and high impedance and low bias |
| Inclosure Material: |
| Metal |
| Inclosure Configuration: |
| Can |
| Input Circuit Pattern: |
| 2 input |
| Design Function And Quantity: |
| 1 amplifier, operational, general purpose |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 18.0 volts power source |
| Terminal Type And Quantity: |
| 8 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |

A458a0