NSN 5962-01-235-1279

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-235-1279

Body Length: 0.290 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.035 inches and 0.085 inches **Maximum Power Dissipation Rating:** 330.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 comparator, voltage **Case Outline Source And Designator:** F-4 mil-m-38510 **Current Rating Per Characteristic:** 50.00 milliamperes forward current, peak total value not applicable **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 36.0 volts power source **Time Rating Per Chacteristic:** 600.00 nanoseconds propagation delay time, low to high level output and 500.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 10 flat leads **Specification Data:** 81349-mil-m-38510/103 government specification

N/a

Shelf Life:

Unit Of Measure:

NSN 5962-01-235-1279

Linear Microcircuit - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A458a0