

View Online at <https://aerobasegroup.com/nsn/5962-01-235-1294>

Body Length:

0.390 inches

Body Width:

Between 0.235 inches and 0.260 inches

Body Height:

Between 0.045 inches and 0.085 inches

Maximum Power Dissipation Rating:

400.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and internally compensated

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Input Circuit Pattern:

2 input

Design Function And Quantity:

1 amplifier, operational, general purpose

Case Outline Source And Designator:

F-2 mil-m-38510

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

22.0 volts power source

Time Rating Per Characteristic:

1200.00 nanoseconds propagation delay time, low to high level output and 1200.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

14 flat leads

Specification Data:

81349-mil-m-38510/101 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0