NSN 5962-01-235-1297

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-235-1297

View Online at https://aerobasegroup.com/hsn/5962-01-255-1297	
Body Length:	
0.405 inches	
Body Width:	
Between 0.220 inches and 0.310 inches	
Body Height:	
0.140 inches	
Maximum Power Dissipation Rating:	
370.0 milliwatts	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
-65.0/+150.0 degrees celsius	
Features Provided:	
Hermetically sealed and monolithic and w/reset	
Inclosure Material:	
Ceramic and glass	
Inclosure Configuration:	
Dual-in-line	
Input Circuit Pattern:	
3 input	
Design Function And Quantity:	
1 timer	
Case Outline Source And Designator:	
D-4 mil-m-38510	
Terminal Surface Treatment:	
Solder	
Voltage Rating And Type Per Characteristic:	
18.0 volts power source	
Time Rating Per Chacteristic:	
900.00 nanoseconds propagation delay time, low to high level output	
Test Data Document:	
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification type	ication
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	۱
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Terminal Type And Quantity:	
8 printed circuit	
Specification Data:	
81349-mil-m-38510/109 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	

Yes - demil/mli

NSN 5962-01-235-1297

Linear Microcircuit - Page 2 of 2

Fiig: A458a0

