NSN 5962-01-235-1310

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-235-1310

Body Length:
0.440 inches
Body Width:
Between 0.245 inches and 0.285 inches
Body Height:
Between 0.045 inches and 0.085 inches
Maximum Power Dissipation Rating:
176.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and monolithic and low power and schottky and w/clear
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
9 input
Design Function And Quantity:
1 counter, binary 4 bit async
Case Outline Source And Designator:
F-5 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
16 flat leads
Specification Data:
81349-mil-m-38510/315 government specification
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

NSN 5962-01-235-1310

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0