NSN 5962-01-235-1329

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-235-1329

| View Online at https://a | aerobasegroup.com/nsn/5962-01-235-1329 |
|---------------------------|--|
| Body Length: | |
| 0.390 inches | |
| Body Width: | |
| 0.260 inches | |
| Body Height: | |
| 0.085 inches | |
| Maximum Power Diss | ipation Rating: |
| 25.0 milliwatts | |
| Operating Tempuratu | re Range: |
| -55.0/+125.0 degrees of | elsius |
| Storage Tempurature | Range: |
| -65.0/+150.0 degrees o | elsius |
| Features Provided: | |
| Monolithic and schottky | / and low power |
| Inclosure Material: | |
| Ceramic | |
| Inclosure Configuration | on: |
| Flat pack | |
| Output Logic Form: | |
| Transistor-transistor log | gic |
| Input Circuit Pattern: | |
| Dual 4 input | |
| Design Function And | Quantity: |
| 2 flip-flop, d-type | |
| Case Outline Source | And Designator: |
| F-2 mil-m-38510 | |
| Terminal Surface Trea | atment: |
| Solder | |
| Voltage Rating And T | ype Per Characteristic: |
| 7.0 volts power source | |
| Test Data Document: | |
| 81349-mil-m-38510 sp | ecification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes comr | nercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| | formance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Q | |
| 14 flat leads | |
| Specification Data: | |
| - | 1 government specification |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| Yes - demil/mli | |
| | |

NSN 5962-01-235-1329

Digital Microcircuit - Page 2 of 2

Fiig: A458a0

