# NSN 5962-01-235-2421

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-235-2421

## Body Length:

0.390 inches

## Body Width:

Between 0.235 inches and 0.260 inches

## **Body Height:**

Between 0.045 inches and 0.085 inches

## **Maximum Power Dissipation Rating:**

88.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **Features Provided:**

Hermetically sealed and burn in and monolithic and positive outputs and schottky and cascadable and positive edge triggered

#### Inclosure Material:

Ceramic

#### Inclosure Configuration:

Flat pack

#### **Output Logic Form:**

Transistor-transistor logic

## Input Circuit Pattern:

Dual 4 input

#### **Design Function And Quantity:**

2 generator, baud rate

## Case Outline Source And Designator:

F-2 mil-m-38510

## **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

7.0 volts power source

## **Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

14 flat leads

## **Specification Data:**

81349-mil-m-38510/341 government specification

#### Shelf Life:

N/a

#### Unit Of Measure:

## Demilitarization:

Yes - demil/mli

# NSN 5962-01-235-2421

Digital Microcircuit - Page 2 of 2

**Fiig:** A458a0

