## NSN 5962-01-235-2431

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-235-2431 **Body Length:** 0.785 inches **Body Width:** 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 115.5 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and low power and schottky **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Hex 1 input **Design Function And Quantity:** 6 inverter **Case Outline Source And Designator:** D-1 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Test Data Document:** 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 14 printed circuit **Specification Data:** 81349-mil-m-38510/313 government specification Shelf Life: N/a

Yes - demil/mli

**Unit Of Measure:** 

**Demilitarization:** 

## NSN 5962-01-235-2431

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0