NSN 5962-01-235-2436

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-235-2436

view Online at https://aeiobasegi	
Body Length:	
0.840 inches	
Body Width:	
Between 0.220 inches and 0.310	nches
Body Height:	
0.140 inches	
Maximum Power Dissipation Ra	ting:
55.0 milliwatts	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
65.0/+150.0 degrees celsius	
Features Provided:	
ow power and schottky and w/en	able and cascadable and w/strobe
nclosure Material:	
Ceramic and glass	
nclosure Configuration:	
Dual-in-line	
Dutput Logic Form:	
ransistor-transistor logic	
nput Circuit Pattern:	
2 input	
Design Function And Quantity:	
selector, data, multiplexer	
Case Outline Source And Desig	nator:
0-2 mil-m-38510	
erminal Surface Treatment:	
Solder	
oltage Rating And Type Per Cl	naracteristic:
0.5 volts power source and 7.0 v	olts power source
Fest Data Document:	
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial cata	alogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance re	equirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:	
16 printed circuit	
Specification Data:	
31349-mil-m-38510/309 governme	ent specification
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	

Yes - demil/mli

NSN 5962-01-235-2436

Digital Microcircuit - Page 2 of 2

Fiig: A458a0

