

View Online at <https://aerobasegroup.com/nsn/5962-01-235-2438>

Body Length:

0.875 inches

Body Width:

0.250 inches

Body Height:

0.185 inches

Maximum Power Dissipation Rating:

88.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic and low power and schottky and 3-state output and cascadable

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Quad 2 input

Design Function And Quantity:

4 selector, data, multiplexer

Case Outline Source And Designator:

D-2 mil-m-38510

Current Rating Per Characteristic:

18.00 milliamperes forward current, nonrepetitive, peak total value minor

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

16 printed circuit

Specification Data:

81349-mil-m-38510/309 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0