

View Online at <https://aerobasegroup.com/nsn/5962-01-235-2485>

Body Length:

0.640 inches

Body Width:

Between 0.360 inches and 0.420 inches

Body Height:

Between 0.045 inches and 0.090 inches

Maximum Power Dissipation Rating:

200.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and monolithic and positive outputs

Inclosure Material:

Ceramic

Inclosure Configuration:

Flat pack

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

Dual 7 input

Design Function And Quantity:

2 latch

Case Outline Source And Designator:

F-6 mil-m-38510

Time Rating Per Characteristic:

400.00 nanoseconds propagation delay time, low to high level output and 400.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-m-38510/176 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0