NSN 5962-01-235-3495

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-235-3495

Body Length:
1.060 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.130 inches and 0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and w/clock and w/clear
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
10 input
Design Function And Quantity:
8 flip-flop, d-type, clocked
Case Outline Source And Designator:
D-8 mil-m-38510
Current Rating Per Characteristic:
-25.00 milliamperes output sink and 25.00 milliamperes output sink
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
240.00 nanoseconds propagation delay time, low to high level output and 240.00 nanoseconds propagation delay time, high to low leve
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
20 printed circuit
Shelf Life:

--

N/a

Unit Of Measure:

NSN 5962-01-235-3495

Digital Microcircuit - Page 2 of 2



Demilitarization:

No

Fiig:

A458a0