# NSN 5962-01-235-6356

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-235-6356

# **Body Length:**

Between 0.755 inches and 0.785 inches

# Body Width:

Between 0.245 inches and 0.280 inches

# **Body Height:**

0.180 inches

## **Maximum Power Dissipation Rating:**

1.0 watts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+175.0 degrees celsius

## **Features Provided:**

Hermetically sealed and burn in and w/resistor and monolithic

#### Inclosure Material:

Ceramic

## Inclosure Configuration:

Dual-in-line

## Input Circuit Pattern:

Quad 2 input

# **Design Function And Quantity:**

4 receiver, line

## Case Outline Source And Designator:

To-116 joint electron device engineering council

## **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

10.0 volts power source

## Time Rating Per Chacteristic:

85.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

## **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

## Terminal Type And Quantity:

14 printed circuit

#### Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0