

View Online at <https://aerobasegroup.com/nsn/5962-01-235-6961>

**Body Length:**

0.785 inches

**Body Width:**

Between 0.220 inches and 0.310 inches

**Body Height:**

0.140 inches

**Maximum Power Dissipation Rating:**

200.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+175.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

Dual 4 input

**Design Function And Quantity:**

2 gate, nor

**Case Outline Source And Designator:**

D-1 mil-m-38510

**Time Rating Per Characteristic:**

315.00 nanoseconds propagation delay time, low to high level output and 315.00 nanoseconds propagation delay time, high to low level output

**Precious Material And Location:**

Terminal surfaces gold

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-m-38510/52 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0