NSN 5962-01-235-7848

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-235-7848

| View Online at https://aerobasegroup.com/nsn/5962-01-235-7848 | |
|--|---------------|
| Body Length: | |
| 0.840 inches | |
| Body Width: | |
| 0.310 inches | |
| Body Height: | |
| 0.185 inches | |
| Maximum Power Dissipation Rating: | |
| 110.0 milliwatts | |
| Operating Tempurature Range: | |
| -55.0/+125.0 degrees celsius | |
| Storage Tempurature Range: | |
| -65.0/+150.0 degrees celsius | |
| Features Provided: | |
| Monolithic and schottky and low power | |
| Inclosure Material: | |
| Ceramic | |
| nclosure Configuration: | |
| Dual-in-line | |
| Output Logic Form: | |
| Transistor-transistor logic | |
| Input Circuit Pattern: | |
| 6 input | |
| Design Function And Quantity: | |
| 1 decoder | |
| Case Outline Source And Designator: | |
| D-2 mil-m-38510 | |
| Terminal Surface Treatment: | |
| Solder | |
| Voltage Rating And Type Per Characteristic: | |
| 7.0 volts power source | |
| Test Data Document: | |
| 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in | specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on o | certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | |
| Terminal Type And Quantity: | |
| 16 printed circuit | |
| Specification Data: | |
| 81349-mil-m-38510/337 government specification | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| | |

Yes - demil/mli

NSN 5962-01-235-7848

Digital Microcircuit - Page 2 of 2

Fiig: A458a0

