NSN 5962-01-236-6882



Memory Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-236-6882 **Body Length:** Between 1.230 inches and 1.290 inches **Body Width:** Between 0.510 inches and 0.540 inches **Body Height:** 0.180 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and bipolar and programmed **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 14 input **Terminal Surface Treatment:** Tin **Voltage Rating And Type Per Characteristic:** 5.0 volts input **Time Rating Per Chacteristic:** 65.00 nanoseconds propagation delay time, low to high level output and 65.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Prom **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 24 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A458a0