

View Online at <https://aerobasegroup.com/nsn/5962-01-236-9497>

**Body Length:**

Between 0.885 inches and 0.915 inches

**Body Width:**

Between 0.285 inches and 0.305 inches

**Body Height:**

Between 0.140 inches and 0.170 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

High speed and bipolar and 3-state output and w/enable and schottky

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

12 input

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-0.3 volts power source and 7.0 volts power source

**Time Rating Per Characteristic:**

90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output

**Memory Device Type:**

Rom

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

18 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0