NSN 5962-01-237-3394

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-237-3394

Body Length: 0.785 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 176.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and w/schmitt trigger and positive outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 gate, nand **Case Outline Source And Designator:** D-1 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 22.00 nanoseconds propagation delay time, low to high level output and 22.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a

Demilitarization:

Unit Of Measure:

Yes - demil/mli

NSN 5962-01-237-3394

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0