

View Online at <https://aerobasegroup.com/nsn/5962-01-237-4036>

Body Length:

0.960 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

0.140 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and electrostatic sensitive and w/enable and w/clock

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

5 input

Criticality Code Justification:

Feat

Design Function And Quantity:

1 encoder

Case Outline Source And Designator:

D-6 mil-m-38510

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

18.0 volts power source

Time Rating Per Characteristic:

150.00 nanoseconds propagation delay time, low to high level output and 150.00 nanoseconds propagation delay time, high to low level output

Special Features:

Nuclear hardness critical item

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

18 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0