NSN 5962-01-237-4038

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-237-4038

Body Length: 0.960 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and w/clock and w/reset **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 11 input **Design Function And Quantity:** 1 generator, clock **Case Outline Source And Designator:** D-6 mil-m-38510 **Terminal Surface Treatment:**

Solder

Voltage Rating And Type Per Characteristic:

8.0 volts power source

Special Features:

Nuclear hardness critical item; no drawing to determine if isc code item should also be nuclear hardness. Can't change criticality code to

reflect nuclear hardness

Test Data Document:

14933-84068 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

18 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-01-237-4038

Digital Microcircuit - Page 2 of 2

Fiig: A458a0

