

View Online at <https://aerobasegroup.com/nsn/5962-01-237-7384>

Body Length:

0.785 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

0.140 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and high speed

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

Quad 2 input

Design Function And Quantity:

4 gate, exclusive or

Case Outline Source And Designator:

D-1 mil-m-38510

Current Rating Per Characteristic:

-25.00 milliamperes collector cutoff current, dc, with specified resistance between base and emitter and 25.00 milliamperes reverse current, dc

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

2.0 volts power source and 6.0 volts power source

Time Rating Per Characteristic:

180.00 nanoseconds propagation delay time, low to high level output and 180.00 nanoseconds propagation delay time, high to low level output

Special Features:

Nuclear hardness critical items

Nuclear Hardness Critical Feature:

Hardened

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A458a0