## NSN 5962-01-238-6827



Linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-238-6827 **Body Length:** 1.480 inches **Body Width:** Between 0.520 inches and 0.610 inches **Body Height:** 0.140 inches **Maximum Power Dissipation Rating:** 400.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and w/enable and monolithic **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 16 channel and 20 input **Design Function And Quantity:** 1 multiplexer/demultiplexer, cmos **Terminal Surface Treatment:** Tin Voltage Rating And Type Per Characteristic: 22.0 volts power source and 44.0 volts power source **Time Rating Per Chacteristic:** 1000.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 28 printed circuit Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

Fiig:

A458a0