

View Online at <https://aerobasegroup.com/nsn/5962-01-238-6840>

Body Length:

2.096 inches

Body Width:

Between 0.590 inches and 0.620 inches

Body Height:

0.165 inches

Maximum Power Dissipation Rating:

1.5 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Los angeles class ssn (688); sonar, an/bsy- (v); spruance class dd (963); aircraft, b-2 bomber (atb ; torpedo, adcap 48; tactical aircrew combat training sys (tacts); fire control system, missile mk 74 (fcs) ; nimitz class cvn; seawolf class ssn; tarawa class lha

Features Provided:

Hermetically sealed and w/preset and burn in, mil-std-883, class d

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

30 input

Design Function And Quantity:

1 control, system

Case Outline Source And Designator:

D-5 mil-m-38510

Terminal Surface Treatment:

Tin

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

40 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0