NSN 5962-01-238-6843

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-238-6843

Body Length: 1.060 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.140 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Electrostatic sensitive and w/enable and hermetically sealed **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 10 input **Criticality Code Justification:** Feat **Design Function And Quantity:** 8 buffer, inverting **Case Outline Source And Designator:** D-8 mil-m-38510 **Time Rating Per Chacteristic:** 37.00 nanoseconds propagation delay time, low to high level output and 37.00 nanoseconds propagation delay time, high to low level output **Special Features:** Hardness critical item **Nuclear Hardness Critical Feature:** Hardened **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No

NSN 5962-01-238-6843

Digital Microcircuit - Page 2 of 2

Fiig: A458a0

