

View Online at <https://aerobasegroup.com/nsn/5962-01-238-9584>

Body Length:

Between 0.165 inches and 0.185 inches

Body Outside Diameter:

Between 0.335 inches and 0.370 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Burn in, mil-std-883, class b and high performance and low level and low level and hermetically sealed

Inclosure Material:

Metal

Inclosure Configuration:

Can

Input Circuit Pattern:

4 input

Design Function And Quantity:

2 amplifier, operational, linear

Case Outline Source And Designator:

To-99 joint electron device engineering council

Current Rating Per Characteristic:

50.00 nanoamperes peak forward surge current not applicable

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

22.0 volts power source

Time Rating Per Characteristic:

300.00 nanoseconds rise transient

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0