NSN 5962-01-239-1945

Memory Microcircuit - Page 1 of 2

Yes - demil/mli



View Online at https://aerobasegroup.com/nsn/5962-01-239-1945

_	
Body Length:	
1.485 inches	
Body Width:	
0.600 inches	
Body Height:	
0.175 inches	
Maximum Power Dissipation Rating:	
790.0 milliwatts	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
-65.0/+150.0 degrees celsius	
Features Provided:	
Hermetically sealed and burn in and programmable and ultraviolet erasable and high speed	
Inclosure Material:	
Ceramic	
nclosure Configuration:	
Dual-in-line	
Output Logic Form:	
N-type metal oxide-semiconductor logic	
Input Circuit Pattern:	
16 input	
Ferminal Surface Treatment:	
Solder	
Voltage Rating And Type Per Characteristic:	
5.0 volts power source	
Time Rating Per Chacteristic:	
250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propa	agation delay time, high to low level
putput	
Memory Device Type:	
Rom	
Memory Capacity:	
Unknown	
Test Data Document:	
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer stan	dards, etc.).
Terminal Type And Quantity:	
28 printed circuit	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 5962-01-239-1945

Memory Microcircuit - Page 2 of 2

Fiig: A458a0

