NSN 5962-01-239-2155

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-239-2155 **Body Length:** 1.060 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 300.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and bipolar and programmable **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 16 input **Case Outline Source And Designator:** D-8 mil-m-38510 **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 12.0 volts power source **Time Rating Per Chacteristic:** 75.00 nanoseconds propagation delay time, low to high level output and 75.00 nanoseconds propagation delay time, high to low level output **Memory Device Type: Test Data Document:** 14933-85065 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 20 printed circuit Shelf Life: N/a

Yes - demil/mli

Unit Of Measure:

Demilitarization:

NSN 5962-01-239-2155

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0