## NSN 5962-01-240-5121

Digital-linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-240-5121 **Body Length:** 0.785 inches **Body Width:** 0.310 inches **Body Height:** 0.185 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius **End Application:** B-1 aircraft support equipment. Landing craft air cushion (Icac). Mk 48 torpedo. Hh-60h search and rescue, sh-60f asw carrier based, helicopters. Mx peacekeeper missle support equipment. F100-pw-200 (f-16a/b/c/d) aircraft engine. (aim-9) sidewinder intercept air missle. Los angeles class ssn (688). **Features Provided:** Monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 4 input **Criticality Code Justification:** Feat **Design Function And Quantity:** 1 converter **Case Outline Source And Designator:** D-1 mil-m-38510 **Terminal Surface Treatment:** Voltage Rating And Type Per Characteristic: 36.0 volts power source **Special Features:** Weapon system essential **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 14 printed circuit Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5962-01-240-5121

Digital-linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0