NSN 5962-01-240-5122

Linear Microcircuit - Page 1 of 1

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-240-5122 **Body Length:** Between 0.342 inches and 0.358 inches **Body Width:** Between 0.342 inches and 0.358 inches **Body Height:** Between 0.064 inches and 0.100 inches **Maximum Power Dissipation Rating:** 300.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and negative outputs and positive outputs **Inclosure Material:** Ceramic or metal **Inclosure Configuration:** Leadless flat pack **Input Circuit Pattern:** 3 input **Design Function And Quantity:** 1 amplifier, sample/hold **Case Outline Source And Designator:** C-2 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 40.0 volts power source **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 leadless Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli