

View Online at <https://aerobasegroup.com/nsn/5962-01-240-5628>

Body Length:

0.785 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

0.140 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and high speed and w/clear and w/clock

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

Dual 2 input

Design Function And Quantity:

2 counter, binary

Case Outline Source And Designator:

D-1 mil-m-38510

Current Rating Per Characteristic:

160.00 microamperes supply

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Special Features:

Nuclear hardness critical item; can't change criticality code to reflect nuclear hardness because there is no drawing to determine if isc code 1 item is also nuclear hardness

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0