NSN 5962-01-240-9247

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-240-9247

| view Online at https://aerobasegroup.com/hsr//5962-01-240-9247 |
|--|
| Body Length: |
| 1.400 inches |
| Body Width: |
| 0.540 inches |
| Body Height: |
| 0.150 inches |
| Maximum Power Dissipation Rating: |
| 1.0 watts |
| Operating Tempurature Range: |
| +0.0/+70.0 degrees celsius |
| Storage Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| End Application: |
| Computer, digital cp-1769/g |
| Features Provided: |
| High performance and low power and w/storage and w/clock and w/buffered output |
| Inclosure Material: |
| Plastic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| N-type metal oxide-semiconductor logic |
| nput Circuit Pattern: |
| 14 input |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 7.0 volts power source |
| Time Rating Per Chacteristic: |
| 250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level |
| output |
| Memory Device Type: |
| Rom |
| Memory Capacity: |
| Unknown |
| Terminal Type And Quantity: |
| 24 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| Demilitarization: |
| |

Yes - demil/mli

NSN 5962-01-240-9247

Memory Microcircuit - Page 2 of 2

Fiig: A458a0

