NSN 5962-01-241-9881

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-241-9881

Body Length: 0.360 inches Body Width: 0.360 inches Body Height: 0.100 inches Body Down Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: 55.0/+150.0 degrees celsius Body Midth: 65.0/+150.0 degrees celsius Feature Provided: Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Soldor 2 input Voltage Rating And Type Per Characteristic: 2 input Voltage Rating And Type Per Characteristic: 2 input Sold Sold Sold Sold Sold Sold Sold Sold	0.360 inches Body Width: 0.360 inches Body Heigh: 0.360 inches Body Heigh: 0.100 inches Body Heigh: 0.100 inches Maximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -50.0 degrees Celsius Storage Tem
Body Width: 0.360 inches 0.360 inches 0 Body Height: 0 0.100 inches 0 Body Midwatts 0 000 millivatts 0 Operating Tempurature Range: 0 0.50 /v150.0 degrees celsius 0 Storage Tempurature Range: 0 0.50 /v150.0 degrees celsius 0 Features Provided: 0 Monolithic and high speed and electrostatic sensitive 0 Inclosure Material: 0 Ceramic 0 Inclosure Material: 0 Data Configuration: 0 Leadless flat pack 0 Input Circuit Pattern: 0 2 input 0 Voltage Rating And Type Per Characteristic: 0 2 outputs power source and 20.0 volts power source 0 Values Asiany specification, standard or other document that may be referenced in a basic governing drawing, with as a contractor drawing, original equipment manufacturer drawing, et and asic governing drawing in the solid grawing in the solid	Body Width: 0.360 inches Body Height: 0.100 inches Maximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55 0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Preating Tempurature Range: -65.0/+150.0 degrees celsius Preatures Provided: Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Disign Function And Quantity: 1 amplifier, operational, high speed Solder Values Rating And Type Per Characteristic:
0.300 inches Body Height: 0.100 inches Body Height: 0.100 inches Maximum Powe Dissipation Rating: So0. milliwatis Operating Tempurature Range: -5.04.150.0 degrees celsius Storage Tempurature Range: -5.04.150.0 degrees celsius Code grees cels	Outpoint Body Heigh: 0.100 inches Maximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed 1 amplifier, operational, high speed Stoder Voltage Rating And Type Per Characteristic:
Body Height: 0.100 inches Maximum Power Dissipation Rating: 0.00000000000000000000000000000000000	Body Heigh: 0.100 inches Maximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceramic Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Values Rating And Type Per Characteristic:
0.100 inches Maximum Power Dissipation Rating: 5000 milliwatts Operating Tempurature Range: -56.01+152.0 degrees celsius Storage Tempurature Range: -65.01+152.0 degrees celsius Storage Tempurature Range: -65.01+152.0 degrees celsius Features Provided: Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadess flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -20.0 volts power source and 20.0 volts power source Test Data Document: 13499-551-1153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacture drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing. 20 leadles: Sheft Life: Na Min Chaesure: 20 leadles: Sheft Life: Na Min Chaesure: 	0.100 inches Maximum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Votage Rating And Type Per Characteristic:
Axinum Power Dissipation Rating: Solo milliwats Operating Tempurature Range: Solo Milliwats > 55.04152.0 degrees celsius Storage Tempurature Range: > 65.04150.0 degrees celsius Storage Tempurature Range: > 65.04150.0 degrees celsius Storage Tempurature Range: > Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceranic Inclosure Configuration: Lacadess flat pack Inclosure Configuration: Lacadess flat pack Input Circuit Pattern: 2 input Input Circuit Pattern: 2 input Circuit Pattern: Input Circuit Pattern: 2 input Circuit Pattern: Input Circuit Pattern: 2 input Circuit Pattern: Input	Maxinum Power Dissipation Rating: 500.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+126.0 degrees celsius Features Provided: Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Values Rating And Type Per Characteristic:
S0.0 milliwats Operating Tempurature Range: -55.0/+125.0 degrees celsius Storag Tempurature Range: -68.0/+125.0 degrees celsius Features Provided: Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -20.0 volts power source and 20.0 volts power source Terminal Surface Treatment: -20.0 volts power source and 20.0 volts power source Test Data Document: -20.0 volts power source and 20.0 volts power source Test Data Document: -20.0 volts power source and 20.0 volts power source Test Data Document: 2 leadless Shelf Life: Na Life: Na Life: Na Life: Na Life: Na Life:	S00.0 milliwats Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
Operating Tempurature Range:	Operating Tempurature Range:-55.0/+125.0 degrees celsiusStorage Tempurature Range:-65.0/+150.0 degrees celsius-65.0/+150.0 degrees celsiusFeatures Provided:Monolithic and high speed and electrostatic sensitiveInclosure Material:CeramicCeramicInclosure Configuration:Leadless flat packInput Circuit Pattern:2 inputDesign Function And Quantity:1 amplifier, operational, high speedTerminal Surface Treatment:SolderVotage Rating And Type Per Characteristic:
 Sb.0/4125.0 degrees celsius Sborage Tempurature Range: -65.0/4150.0 degrees celsius Features Provided: Monolitic and high speed and electrostatic sensitive Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating and Yupe Per Characteristic: -20.0 volts power source and 20.0 volts power source Test Data Document: 1 3499-351-1153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etcle actudes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 10 a contractor drawing. 10 a contractor drawing. 11 a contractor drawing. 12 a contractor drawing. 13 a contractor drawing. 14 a contractor drawing. 14 a contractor drawing. 15 a contractor drawing. 16 a contractor drawing. 17 a contractor drawing. 18 a contractor drawing. 19 a contractor drawing. 19 a contractor drawing. 10 a contractor drawing. 10 a contractor drawing. 11 a contractor drawing. 12 a contractor drawing. 13 a contractor drawing. 14 a contractor drawing. 14 a contractor drawing. 15 a contractor drawing. 16 a contractor drawing. 17 a contractor drawing. 18 a contractor drawing. 19 a contractor drawing. 19 a contractor drawing. 10 a contractor drawing. 11 a contractor drawing. 11 a contractor drawing. 12 a contractor drawing. 13 a contractor drawing. 14 a contractor drawing. 14 a contractor drawing. 15 a contractor drawing.	-55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Features Provided: Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Vottage Rating And Type Per Characteristic:
Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Providee: Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.0 volts power source and 20.0 volts power source Test Data Document: 1 3499-351-1153 drawing (his is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, edu excludes any specification, standard or other document that may be referenced in a basic governing drawing, edu excludes any specification, standard or other document that may be referenced in a basic governing drawing, edu excludes any specification, standard or other document that may be referenced in a basic governing drawing, edu excludes any specification, standard or other document that may be referenced in a basic governing drawing, edu excludes any specification, standard or other document that may be referenced in a basic governing drawing, edu excludes any specification, standard or other document that may be referenced in a basic governing drawing, edu excludes any specification, standard or other document that may be referenced in a basic governing drawing, edu excludes any specification, standard or other document that may be referenced in a basic governing drawing, edu excludes and specification, standard or other document that may be referenced in a basic governing drawing, edu excludes and specification, standard or other document that may be referenced in a basic governing drawing Not of Measure: 	Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provide: Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceramic Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Vottage Rating And Type Per Characteristic:
-65.0/+150.0 degrees celsius Features Provided: Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -20.0 volts power source and 20.0 volts power source Test Data Document: 13499-331-1153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etcles excluses any specification, standard or other document that may be referenced in a basic governing drawing; etcle excluses any specification, standard or other document that may be referenced in a basic governing drawing; etcle excluses any specification, standard or other document that may be referenced in a basic governing drawing; etcle excluses any specification, standard or other document that may be referenced in a basic governing drawing; etcle excluses any specification, standard or other document that may be referenced in a basic governing drawing; etcle excluses any specification, standard or other document that may be referenced in a basic governing drawing; Vint Of Measure: - - - Point Intreaction: - - <td>-65.0/+150.0 degrees celsius Features Provided: Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:</td>	-65.0/+150.0 degrees celsius Features Provided: Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
Features Provided: Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -20.0 volts power source and 20.0 volts power source Text Data Document: 13499-331-1153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etclose any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 20 leadless Shelf Life: Na Via Dialeast Shelf Life: Na Unt Of Measure: - Penillitarization: Yes - demil/mil	Features Provided: Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceramic Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -20.0 volts power source and 20.0 volts power source Test Data Document: 13499-351-1153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc Alge Basic Governing drawing (such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc Alge Basic Governing drawing (such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Excludes Disclass Chef Life: N/a Disclass Chef Life:	Monolithic and high speed and electrostatic sensitive Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
Iclosure Material: Ceramic Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Imput Circuit Pattern: 2 Kode Voltage Rating And Type Per Characteristic: 2 Solder Voltage Nating (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. 3 Aph9-351-1153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. 2 leadless Sheff Life: 2 leadles Sheff Life: N/a Chi Of Measure: - - Patteriation: Yot Of Measure: - - Patteriation: - - - - - - - - - - - - - - - - <	Inclosure Material: Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder
Ceramic Inclosure Configuration: Leadless flat pack Leadless flat pack Input Circuit Pattern: 2 input 2 input 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -20.0 volts power source and 20.0 volts power source Test Data Document 13499-351-1153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etcl excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 20 leadless Sheff Life: N/a Unit Of Measure: Demilltarization: Yes - demil/mli	Ceramic Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
Iclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -20.0 volts power source and 20.0 volts power source Test Data Document: 13499-351-1153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etcle excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilltarization: Yes - demil/mii	Inclosure Configuration: Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder
Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -20.0 volts power source and 20.0 volts power source Test Data Document: 13499-351-1153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etcle actudes any specification, standard or other document that may be referenced in a basic governing drawing. 20 leadless Sheff Life: N/a Uht Of Measure: - Design Life: N/a Dinilitarization: Yes - demil/mli	Leadless flat pack Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
Input Circui Pattern: input 2 input Design Function And Quantity: 1 amplifier, operational, high speed Imput Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -20.0 volts power source and 20.0 volts power source Imput Surface Treatment: 13499-351-1153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: Imput Surface Surface 20 leadless Shelf Life: N/a Imput Surface Surface Int Of Measure: Imput Surface Imput Surface Imput Surface Imput Surface Imput Surface Imput Surface Imput Surface Imput Surface Surface Imput Surface Surface Surface Imput Surface Surface Surfac	Input Circuit Pattern: 2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder
2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -20.0 volts power source and 20.0 volts power source Test Data Document: 13499-351-1153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etcl excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	2 input Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
Pesign Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -20.0 volts power source and 20.0 volts power source Test Data Document: 13499-351-1153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etcle excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Pemilitarization: Yes - demil/mli	Design Function And Quantity: 1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -20.0 volts power source and 20.0 volts power source Test Data Document: 13499-351-1153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	1 amplifier, operational, high speed Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -20.0 volts power source and 20.0 volts power source Test Data Document: 13499-351-1153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
Solder Voltage Rating And Type Per Characteristic: -20.0 volts power source and 20.0 volts power source -20.0 volts power source and 20.0 volts power source -20.0 volts power source and 20.0 volts power source -21.153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc -22.0 voltage Rating And Quantity: -23.0 voltage Rating And Quantity: -24.0 voltage Rating And Quantity: -25.0 voltage Rating And Quantity: -25.0 voltage Rating	Solder Voltage Rating And Type Per Characteristic:
Voltage Rating And Type Per Characteristic: -20.0 volts power source and 20.0 volts power source Test Data Document: -20.0 volts is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. 13499-351-1153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. -20.0 volts power source 12499-351-1153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. -20.0 volts power source 120 leadless	Voltage Rating And Type Per Characteristic:
-20.0 volts power source and 20.0 volts power source Test Data Document: 13499-351-1153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etcl excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
Test Data Document: 13499-351-1153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etcle excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	-20.0 volts power source and 20.0 volts power source
13499-351-1153 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
Terminal Type And Quantity: 20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
20 leadless Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
Unit Of Measure: Demilitarization: Yes - demil/mli	
 Demilitarization: Yes - demil/mli	
Yes - demil/mli	Unit Of Measure:
Yes - demil/mli	
Fiig:	
A458a0	-