## NSN 5962-01-243-3977

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-243-3977

## **Body Length:** 0.927 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.140 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** High current and high voltage and high power and hermetically sealed **Inclosure Material:** Glass and metal **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 8 input **Design Function And Quantity:** 8 array, darlington transistor **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 95.0 volts power source **Time Rating Per Chacteristic:** 1000.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 18 printed circuit Shelf Life: Unit Of Measure:

**Demilitarization:** 

Yes - demil/mli

Fiig:

N/a

---

A458a0