NSN 5962-01-243-5973

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-243-5973

| Overall Height: |
|---|
| 0.330 inches |
| Body Length: |
| 0.975 inches |
| Body Width: |
| 0.300 inches |
| Body Height: |
| 0.180 inches |
| Maximum Power Dissipation Rating: |
| 135.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and 3-state output and positive outputs |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 10 input |
| Design Function And Quantity: |
| 8 buffer and 2 driver, line |
| Current Rating Per Characteristic: |
| 50.00 milliamperes reverse current, dc absolute |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 7.0 volts power source |
| Time Rating Per Chacteristic: |
| 30.00 nanoseconds delay |
| Terminal Type And Quantity: |
| 20 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| Yes - demil/mli |

NSN 5962-01-243-5973

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0